

TRIO.BAS MONO cable

TRIO.BAS™

ORUM INTERNATIONAL
© ALL RIGHTS RESERVED



Single aspirating head air sampler with Bluetooth
and cable for charging



- 100 or 200 litres per minute flow rate model
- Battery charger via cable (110/240 volt)
- Bluetooth for data transfer
- Manual or automatic mode
- Official calibration certificate
- Operator/Administrator cascade passwords
- May be used for compressed gas testing in conjunction with gas system
- Stable on a work surface in a vertical position without the use of any external support

DESCRIPTION

- Main customers are pharmaceutical aseptic filling suites, cleanroom, biotech, IVF clinic, operating theatre, hospital pharmacies, blood banks, clinic, microbiological labs, HVAC building monitoring, environmental labs, healthcare ambient monitoring and health authorities.
- A barcode module, thanks to the use of a scanner (barcode reader) with Bluetooth, automatically records the operator, place and plates used for the sampling. The data collected by the barcode reader is transmitted directly to the instrument. This solution is useful for those who already use culture plates with barcode or 2-D barcode (QR Quick Response Code). The data collected is transferred via Bluetooth from the air sampler to a PC or laptop via a dedicated software installed.
- The data is transferred via Bluetooth between the air sampler and a smartphone or tablet (Android version) and then to a PC or laptop.
- The data may be transferred via cable, too. This is helpful for all companies that, due to internal policy, are not allowed to use wireless transfer.
- It is possible to work either in manual or automatic mode.
- The sampler is IP65 certified.
- The battery is recharged by a power cable connected directly to the air sampler.
- The 200 lts/min air flow reduces the operator time and the time sampling.
- The use of sterile Daily Shift aspirating heads reduces the risk of contamination.

PERFORMANCES

- Light weight, ergonomic and balanced design to facilitate handling with or without gloved hands
- Technopolymer shockproof body with antibacterial performances of surfaces
- Compliant according EN/ISO 14698-1, GMP and GLP
- Stainless steel aspirating head with quick bayonet closure, identification number and stainless steel cover to prevent contamination
- Volume of aspirated air: 100 or 200 l/m
- Selected volumes from 30 to 2.000 litres and 17 preset programs
- The aspirating chamber is suitable for 55 mm Contact plates or 90 mm Petri dishes
- Auto calibration: power/flow electronic real time control
- Power supply system: the instrument can be charged continuously by AC powered source 110/240 Volt 50/60 Hz or by rechargeable batteries (inserted inside the air sampler)
- Cycles battery autonomy: 30.000 litres
- IP65 certified protection from dust and water
- Language: English, French, German, Spanish, Italian
- Manual and automatic passwords
- Operative aspirating cycles: manual and automatic
- Memorized data: up to 1.000 samples
- Configuration users and places: 100
- Delayed, remote, start sampling
- Bluetooth connection or cable for data transfer
- Automatic next calibration reminder
- Programmable for compressed gases/air
- Data integrity CFR 21 and GAMP5
- CE mark
- Dimension: 33x16x15h cm
- Weight: 1.440 gr
- Built in ISO 9001 premises

IDENTIFICATION CODES

Code	TRIO.BAS MONO cable PACK (*)
211K	TRIO.BAS MONO 100 Contact PACK with cable (100 litres/min flow rate)
212K	TRIO.BAS MONO 100 Petri PACK with cable (100 litres/min flow rate)
213K	TRIO.BAS MONO 200 Contact PACK with cable (200 litres/min flow rate)
214K	TRIO.BAS MONO 200 Petri PACK with cable (200 litres/min flow rate)

(*) each PACK consists of: 1 air sampler with Bluetooth and battery charger, 1 calibration certificate, 1 s/s ASPI head with s/s cover head, 1 cable for data transfer, 1 robustus carrying case.



TRIO.BAS MONO with cable



Stable on a work surface in a vertical position



Easy manipulation